

PRODUCT INFORMATION (*1)

ROOM AIR CONDITIONER	INDOOR MODEL OUTDOOR MODEL	MSZ-RZ35VU MUZ-RZ35VUHZ
----------------------	-------------------------------	----------------------------

Function (indicate if present)	
cooling	Y
heating	Y

If function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season 'Average'.	
Average (mandatory)	Y
Warmer (if designated)	Y
Colder (if designated)	Y

Item	symbol	value	unit
Design load			
cooling	Pdesignc	3.5	kW
heating/Average	Pdesignh	4.0	kW
heating/Warmer	Pdesignh	2.2	kW
heating/Colder	Pdesignh	5.9	kW

Item	symbol	value	unit
Seasonal efficiency			
cooling	SEER	9.6	-
heating/Average	SCOP/A	5.2	-
heating/Warmer	SCOP/W	6.5	-
heating/Colder	SCOP/C	4.1	-

Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj			
Tj=35°C	Pdc	3.5	kW
Tj=30°C	Pdc	2.6	kW
Tj=25°C	Pdc	1.7	kW
Tj=20°C	Pdc	1.3	kW

Declared energy efficiency ratio, at indoor temperature 27(19) °C and outdoor temperature Tj			
Tj=35°C	EERd	4.6	-
Tj=30°C	EERd	7.0	-
Tj=25°C	EERd	11.5	-
Tj=20°C	EERd	20.2	-

Declared capacity for heating/Average season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	Pdh	3.6	kW
Tj=2°C	Pdh	2.2	kW
Tj=7°C	Pdh	1.4	kW
Tj=12°C	Pdh	1.3	kW
Tj=bivalent temperature	Pdh	4.0	kW
Tj=operating limit	Pdh	3.6	kW

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	COPd	3.4	-
Tj=2°C	COPd	5.2	-
Tj=7°C	COPd	6.5	-
Tj=12°C	COPd	8.2	-
Tj=bivalent temperature	COPd	2.9	-
Tj=operating limit	COPd	1.8	-

Declared capacity for heating/Warmer season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=2°C	Pdh	2.2	kW
Tj=7°C	Pdh	1.4	kW
Tj=12°C	Pdh	1.3	kW
Tj=bivalent temperature	Pdh	2.2	kW
Tj=operating limit	Pdh	3.6	kW

Declared coefficient of performance/Warmer season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=2°C	COPd	5.2	-
Tj=7°C	COPd	6.5	-
Tj=12°C	COPd	8.2	-
Tj=bivalent temperature	COPd	5.2	-
Tj=operating limit	COPd	1.8	-

Declared capacity for heating/Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	Pdh	3.6	kW
Tj=2°C	Pdh	2.2	kW
Tj=7°C	Pdh	1.4	kW
Tj=12°C	Pdh	1.3	kW
Tj=bivalent temperature	Pdh	4.0	kW
Tj=operating limit	Pdh	3.6	kW
Tj=-15°C	Pdh	5.3	kW

Declared coefficient of performance/Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	COPd	3.4	-
Tj=2°C	COPd	5.2	-
Tj=7°C	COPd	6.5	-
Tj=12°C	COPd	8.2	-
Tj=bivalent temperature	COPd	2.9	-
Tj=operating limit	COPd	1.8	-
Tj=-15°C	COPd	2.3	-

Bivalent temperature			
heating/Average	Tbiv	-10	°C
heating/Warmer	Tbiv	2	°C
heating/Colder	Tbiv	-10	°C

Operating limit temperature			
heating/Average	Toi	-30	°C
heating/Warmer	Toi	-30	°C
heating/Colder	Toi	-30	°C

Cycling interval capacity			
for cooling	Pcycc	x	kW
for heating	Pcyhc	x	kW
Degradation co-efficient cooling	Cdc	0.25	-

Cycling interval efficiency			
for cooling	EERcyc	x	-
for heating	COPcyc	x	-
Degradation co-efficient heating	Cdh	0.25	-

Electric power input in power modes other than 'active mode'			
off mode	P _{OFF}	2	W
standby mode	P _{SB}	2	W
thermostat - off mode	P _{TO}	6	W
crankcase heater mode	P _{CK}	0	W

Annual electricity consumption			
cooling	Q _{CE}	127	kWh/a
heating/Average	Q _{HE}	1075	kWh/a
heating/Warmer	Q _{HE}	468	kWh/a
heating/Colder	Q _{HE}	2986	kWh/a

Capacity control (indicate one of three options)	
fixed	N
staged	N
variable	Y

Other items			
Sound power level (indoor/outdoor)	L _{WA}	59/61	dB(A)
Global warming potential	GWP (*2)	3	kgCO ₂ eq.
Rated air flow (indoor/outdoor)	-	846/2322	m ³ /h

Contact details for obtaining more information	MITSUBISHI ELECTRIC CORPORATION SHIZUOKA WORKS 3-18-1, Oshika, Suruga-ku, Shizuoka 422-8528, Japan E-mail: melshierp@MitsubishiElectric.co.jp
--	---

(*1) This information is based on the "product information requirement" in COMMISSION REGULATION (EU) No. 206/2012.
(*2) This GWP value is based on IPCC 4th Assessment Report.

TECHNICAL DOCUMENTATION (1)

ROOM AIR CONDITIONER	INDOOR MODEL	MSZ-RZ35VU	305H*998W*247D (mm)
	OUTDOOR MODEL	MUZ-RZ35VUHZ	714H*800W*285D (mm)

Function	
cooling	Y
heating	Y

The heating season	
Average (mandatory)	Y
Warmer (if designated)	Y
Colder (if designated)	Y

Capacity control	
fixed	N
staged	N
variable	Y

Item	symbol	value	unit
Seasonal efficiency (2)			
cooling	SEER	9.6	-
heating/Average	SCOP/A	5.2	-
heating/Warmer	SCOP/W	6.5	-
heating/Colder	SCOP/C	4.1	-

Energy efficiency class			
cooling	SEER	A+++	-
heating/Average	SCOP/A	A+++	-
heating/Warmer	SCOP/W	A+++	-
heating/Colder	SCOP/C	A+	-

Other items			
Sound power level (indoor/outdoor)	L _{WA}	59/61	dB (A)
Refrigerant	-	R290	-
Global warming potential	GWP (3)	3	kgCO ₂ eq.

identification and signature of the person empowered to bind the supplier	 _____ Kunihiro Morishita Department Manager, Quality Assurance Department MITSUBISHI ELECTRIC CONSUMER PRODUCTS (THAILAND) CO., LTD
---	--

- (1) This information is based on COMMISSION DELEGATED REGULATION (EU) No. 626/2011.
 (2) SEER/SCOP values are measured based on EN 14825:2016: Testing and rating at part load conditions and calculation of seasonal performance.
 (3) This GWP value is based on IPCC 4th Assessment Report.