

INDOOR UNIT ALL IN ONE

FEATURES

- Possibility of control via internet with Comfort Home application
- High efficiency
- Integrated expansion vessel and safety valve
- Circulatory pump with self-regulation of speed
- Possibility of the equitherm control, control by reference room temperature or thermostat
- Silent mode
- Built-in electric cartridge with 3 or 9 kW capacity

MSH-190TB/3
MSH-240TB/3
MSH-190TB-3/9
MSH-240TB-3/9



Possible combinations	
Indoor	Outdoor
MSH-190TB/3	MSH-60EB
MSH-240TB/3	MSH-120EB
MSH-240TB/3	MSH-140EB
MSH-240TB/3	MSH-160EB
MSH-190TB-3/9	MSH-80EB
MSH-190TB-3/9	MSH-100EB
MSH-240TB-3/9	MSH-120EB-3
MSH-240TB-3/9	MSH-140EB-3
MSH-240TB-3/9	MSH-160EB-3

Model MSH-			190TB/3	240TB/3	190TB-3/9	240TB-3/9
Power supply		V / Ph / Hz	220 - 240 / 1 /50		380 - 415 / 3 /50	
Connecting pipe (refrigerant)	Gas	inch / mm			5/8" / 16,0	
	Liquid				3/8" / 9,5	
Connecting pipe (water)	Inlet	inch			1"	
	Outlet					
Safety valve		bar			3	
Leaving water temperature	Cooling	°C			5 - 25	
	Heating	°C			25 - 65	
Main components	Water pump	Type			Inverter	
		Speed			Automatic	
		Max. power			90	
Hot water tank	Volume	l	190	240	190	240
	El. heater	kW			1,5+1,5	
Expansion tank	Volume	l			8	
	Max. pressure	bar			3	
	Pressure	bar			1	
Auxiliary electric heater	Mode	-			Automatic	
	Capacity	kW	3		9	
	Combination	-	3		3+3+3	
	Power supply	V / Ph / Hz	220 - 240 / 1 /50		380 - 415 / 3 /50	
Heat exchanger	Type	-			Brazed plate	
	Amount	-			1	
Level of acoustic pressure in 1m		dB (A)			29	
Dimensions	Outline (w x d x h)	mm	600 x 600 x 1683	600 x 600 x 1943	600 x 600 x 1683	600 x 600 x 1943
	Packaged (w x d x h)	mm	730 x 730 x 1920	730 x 730 x 2180	730 x 730 x 1920	730 x 730 x 2180
Weight	Netto	kg	140	157	140	157
	Brutto	kg	161	178	161	178

YUKON